



GPS TATTLE[™]

SPECIFICALLY DESIGNED FOR:
TRACKING LOCATION AND SPEED OF ASSETS











FEATURES

- ▶ Remotely access the system 24/7 on multiple devices, anytime, from anywhere
- ▶ All assets, in real-time, on one map. With route planning, reports, and update intervals
- ▶ Unlimited user and permission access
- ▶ Notifications sent via text or email alerting tank level percentage



BENEFITS

Fully utilizing all of the features that Tattle Systems[®] has to offer results in proactive insights and informed business decisions that contribute to your businesses bottom line.

- | | |
|--|---|
|  Proven 25% reduction in logistics costs |  Improve client experience |
|  Real-time remote access |  Asset security |
|  Optimize asset management |  Data generation |
|  Optimize inventory levels |  Minimize environmental impact |
|  Optimize employee productivity |  Made in Canada |





GPS TATTLETM

SPECIFICALLY DESIGNED FOR:
TRACKING LOCATION AND SPEED OF ASSETS

PLUG-IN GPS SPECIFICATIONS



DIMENSIONS	119.38mm x 119.38mm x 60.96mm (4.7" x 4.7" x 2.4")
DEVICE MOUNTING	Brackets
WEIGHT	363g (0.8lb)
POWER	12V DC
WIRED INTERFACES	Cigarette Lighter
CABLE LENGTH	5.9ft (1.8m)
RADIO INTERFACES	Connectivity
OPERATING TEMPERATURE	-40C to +60C
ALTITUDE	Up to 2000m
OPERATING HUMIDITY RANGE	Maximum relative humidity 80% for temperatures up to 31C decreasing linearly to 50% relative humidity at 40C
STORAGE TEMPERATURE	-40C to +65C
IP RATING	IP68 (Dust tight, no ingress of dust. Watertight against the effect of immersion in water under pressure for long periods)

BATTERY HOOK-UP GPS SPECIFICATIONS



DIMENSIONS	119.38mm x 119.38mm x 60.96mm (4.7" x 4.7" x 2.4")
DEVICE MOUNTING	Brackets
WEIGHT	363g (0.8lb)
POWER	12V DC
WIRED INTERFACES	Direct Battery Hookups
CABLE LENGTH	6.5ft (2m) or 13.1ft (4m)
RADIO INTERFACES	Connectivity
OPERATING TEMPERATURE	-40C to +60C
ALTITUDE	Up to 2000m
OPERATING HUMIDITY RANGE	Maximum relative humidity 80% for temperatures up to 31C decreasing linearly to 50% relative humidity at 40C
STORAGE TEMPERATURE	-40C to +65C
IP RATING	IP68 (Dust tight, no ingress of dust. Watertight against the effect of immersion in water under pressure for long periods)