







TEMP TATTL

SPECIFICALLY DESIGNED FOR: TEMPERATURE MONITORING IN REMOTE AREAS

FEATURES

- Remotely access the system 24/7 on multiple devices, anytime, from anywhere
- All assets, in real-time, on one map. With route planning, reports, and update intervals
- Unlimited user and permission access
- Notifications sent via text or email alerting tank level percentage



BENEFITS

Fully utilizing all of the features that Tattle Systems® has to offer results in proactive insights and informed business decisions that contribute to your businesses bottom line.



Proven 25% reduction in logistics costs



Improve client experience



Real-time remote access



Asset security



Optimize asset management



Data generation



Optimize inventory levels



Minimize environmental impact



Optimize employee productivity



Made in Canada



















TEMP TATTLE

SPECIFICALLY DESIGNED FOR:
TEMPERATURE MONITORING IN REMOTE AREAS

DEVICE SPECIFICATIONS



DIMENSIONS	152.4mm x 152.4mm x 101.6mm (6" x 6" x 4")
DEVICE MOUNTING	Magnets (brackets by request)
WEIGHT	3.5kg (7.7lb)
POWER	6V DC, 3.5W (via solar)
WIRE INTERFACE	9-pin (external sensor)
CONNECTIVITY	Cellular LTE, LTE-M
OPERATING TEMPERATURE	-40C to +60C
ALTITUDE	Up to 2000m
OPERATING HUMIDITY RANGE	Maximum relative humidity 80% for temperatures up to 31C decreasing linearly to 50% relative humidity at 40C
STORAGE TEMPERATURE	-40C to +65C
IP RATING	IP54 (Protected from limited dust ingress. Protected from water spray from any direction, limited ingress protection.)
CERTIFICATIONS CPS.US	Product Safety QPS Certified for Canada and the United States. Class I, Division 2, Groups C and D, T4 (with alternate markings Class I, Zone 2, IIB, T4 for the US) Radio: This product contains EG91NA FCC ID: XM-R201807EG91NA IC: 10224A-2018EG91NA and BG95M3 FCC ID: XMR201910BG95M3 IC: 10224A-2019BG95M3

SENSOR SPECIFICATIONS



TEMPERATURE RANGES	-55C to +125C
SENSOR SIZE	D = 0.25" (6.35mm) L = 1.5" (38.1mm)
CABLE LENGTH	6ft (1.8m)
CONNECTION	9-pin male plug