



SCAN ME

## FUEL TATTLE GAUGE™

SPECIFICALLY DESIGNED FOR: DIESEL AND GASOLINE TANKS WITH A MECHANICAL FLOAT ARM

### FEATURES

- ▶ Remotely access the system 24/7 on multiple devices, anytime, from anywhere
- ▶ All assets, in real-time, on one map. With route planning, reports, and update intervals
- ▶ Unlimited user and permission access
- ▶ Notifications sent via text or email alerting tank level percentage



### BENEFITS

Fully utilizing all of the features that Tattle Systems® has to offer results in proactive insights and informed business decisions that contribute to your businesses bottom line.



Proven 25% reduction in logistics costs



Improve client experience



Real-time remote access



Asset security



Optimize asset management



Data generation



Optimize inventory levels



Minimize environmental impact



Optimize employee productivity



Made in Canada





# FUEL TATTLE GAUGE™

**SPECIFICALLY DESIGNED FOR:  
DIESEL AND GASOLINE TANKS WITH A  
MECHANICAL FLOAT ARM**



## DEVICE SPECIFICATIONS

<b>DIMENSIONS</b>	152.4mm x 152.4mm x 101.6mm (6" x 6" x 4")
<b>DEVICE MOUNTING</b>	Magnets (brackets by request)
<b>WEIGHT</b>	3.5kg (7.7lb)
<b>POWER</b>	6V DC, 3.5W (via solar)
<b>WIRE INTERFACE</b>	9-pin (external sensor)
<b>CONNECTIVITY</b>	Cellular LTE, LTE-M
<b>OPERATING TEMPERATURE</b>	-40C to +60C
<b>ALTITUDE</b>	Up to 2000m
<b>OPERATING HUMIDITY RANGE</b>	Maximum relative humidity 80% for temperatures up to 31C decreasing linearly to 50% relative humidity at 40C
<b>STORAGE TEMPERATURE</b>	-40C to +65C
<b>IP RATING</b>	IP54 (Protected from limited dust ingress. Protected from water spray from any direction, limited ingress protection.)
<b>CERTIFICATIONS</b>	<p>Product Safety: QPS Certified for Canada and the United States. Class I, Division 2, Groups C and D, T4 (with alternate markings Class I, Zone 2, IIB, T4 for the US)</p> <p>Radio: This product contains EG91NA FCC ID: XM-R201807EG91NA IC: 10224A-2018EG91NA and BG95M3 FCC ID: XMR201910BG95M3 IC: 10224A-2019BG95M3</p>

## DIAL DESCRIPTION

- ▶ Magnetically driven dial
- ▶ A solid-state technology with no moving contacts
- ▶ UV stabilized plastic material
- ▶ Fluorescent - glowing dial numbers in the dark

## SENSOR SPECIFICATIONS

<b>DIAL VOLUME</b>	E, ¼, ½, ¾, F
<b>DIAL SIZES</b>	2" (screw-on mount)
<b>DIAL FASTENERS</b>	2 screws (6 - 32 x 3/8")
<b>CABLE LENGTH</b>	6ft (1.8m)
<b>CONNECTION</b>	9-pin male plug
<b>SENSOR CERTIFICATIONS</b>	UL Classified as intrinsically safe for Class 1, Div 1, Group C&D