



SCAN ME

## LIQUID TATTLE™

SPECIFICALLY DESIGNED FOR:  
LIQUID FERTILIZER, WATER, DIESEL EXHAUST FLUID,  
WASTEWATER, LUBRICANTS AND CHEMICALS

### FEATURES

- ▶ Remotely access the system 24/7 on multiple devices, anytime, from anywhere
- ▶ All assets, in real-time, on one map. With route planning, reports, and update intervals
- ▶ Unlimited user and permission access
- ▶ Notifications sent via text or email alerting tank level percentage



### BENEFITS

Fully utilizing all of the features that Tattle Systems® has to offer results in proactive insights and informed business decisions that contribute to your businesses bottom line.


- Proven 25% reduction in logistics costs
- Improve client experience
- Real-time remote access
- Asset security
- Optimize asset management
- Data generation
- Optimize inventory levels
- Minimize environmental impact
- Optimize employee productivity
- Made in Canada





# LIQUID TATTLE<sup>™</sup>

**SPECIFICALLY DESIGNED FOR:  
LIQUID FERTILIZER, WATER, DIESEL EXHAUST FLUID,  
WASTEWATER, LUBRICANTS AND CHEMICALS**



## DEVICE SPECIFICATIONS

<b>DIMENSIONS</b>	152.4mm x 152.4mm x 101.6mm (6" x 6" x 4")
<b>DEVICE MOUNTING</b>	Magnets (brackets by request)
<b>WEIGHT</b>	3.5kg (7.7lb)
<b>POWER</b>	6V DC, 3.5W (via solar)
<b>WIRE INTERFACE</b>	9-pin (external sensor)
<b>CONNECTIVITY</b>	Cellular LTE, LTE-M
<b>OPERATING TEMPERATURE</b>	-40C to +60C
<b>ALTITUDE</b>	Up to 2000m
<b>OPERATING HUMIDITY RANGE</b>	Maximum relative humidity 80% for temperatures up to 31C decreasing linearly to 50% relative humidity at 40C
<b>STORAGE TEMPERATURE</b>	-40C to +65C
<b>IP RATING</b>	IP54 (Protected from limited dust ingress. Protected from water spray from any direction, limited ingress protection.)
<b>CERTIFICATIONS</b>	<p>Product Safety: QPS Certified for Canada and the United States. Class I, Division 2, Groups C and D, T4 (with alternate markings Class I, Zone 2, IIB, T4 for the US)</p> <p>Radio: This product contains EG91NA FCC ID: XM-R201807EG91NA IC: 10224A-2018EG91NA and BG95M3 FCC ID: XMR201910BG95M3 IC: 10224A-2019BG95M3</p>

## SENSOR SPECIFICATIONS

<b>SENSOR HOUSING</b>	Stainless steel
<b>SENSOR DIMENSIONS</b>	L=6" (166mm) D=1" (27mm)
<b>EXTERNAL INSTALL</b>	½" NPT
<b>PRESSURE RANGE</b>	0...50 PSI
<b>SENSOR CABLE LENGTH</b>	33ft (10m) or 100ft (30m)
<b>AIRBOX CERTIFICATIONS</b>	cULus, NEMA Type 4, 4x, 6, 6P
<b>AIRBOX DIMENSIONS</b>	3" (75mm) x 3 1/8" (80mm) x 2" (52mm)
<b>AIRBOX TO TATTLE CABLE</b>	3ft (1m)
<b>CONNECTION</b>	9-pin male plug